





The Patent Office Concept House Cardiff Road Newport ·

South Wales

NP10 | \$42 QD 0 6 JUL 2004

WIPO


PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before reregistration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 24 June 2004

PRIORITY

COMPLIANCE WITH RULE 17.1(a) OR (b)

REMBINED SERRCH & EXAMINATION REQUESTED

THE PATENT OFFICE Patents Form 2 5 APR 2003 es Aut 1977 (Rule 16) RECEIVED BY FAX



25APR03 E892779-1 C71306 P01/7700 0.00-0309452.1

The Patent Office

Cardelf Road Newport South Wates NP10 8QQ -

Request for grant of a patent

(See the notes on the back of this form, You can also get un explanatory leader from the Potent Office to help you III in this force)

1. Your reference

TB9/61865 -10-80

2. Patent application number (The Petent Office will III in this part)

· 2 5 APR 2003

0309452.1

(Af you know it)

Full name, address and postcode of the or of each applicant (authors all someons) - S GIBBS TECHNOLOGIES LTD. CHAMBERS LA MOTTE

08443731001 Patents ADP number (if you know it) ST. HELIER TERSEY CHANNEL ISLANDS . JEI

If the applicant is a corporate hody, give the country/state of its incorporation

BRITISH VIRGIN TSLANDS ,

Title of the invention

AMPHIBIOUS VEHICLE STEERING

5. Name of your agent (if you have one)

"Address for service" in the United Ringdom to which all correspondence should be sent (including the postcods)

T BAIN SMITH WICKENS MAHOR CHARING

> NR. ASHFORD THEF OPT

Patents ADP mumber (If you know 11)

- 6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (Fyon know k) the or each application number
 - Priority application range

Date of Hing (day/month/year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of Bling (day / socials / year)

- 8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer Yes' H
 - a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.

See mate (d))

Yes

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form Description	, 5	0 .
Claim(s) Abstract	1.2	
Drawing(s)	.4	

10. If you are also filing any of the following. state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Fatents Form 9/77)

Request for substantive examination (Patents Porm 10/77)

Any other documents

FeeSheet

(plance specify)

Signature

Date 4:03

I/We request the grant of a patent on the basis of this application.

12. Name and daytime telephone number of person to contact in the United Kingdom

T.BAIN SMITH

0208 688 8318 01233 712594/P

Warring

11.

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be probblied or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to probibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

10

15

20

25

30

DUPLICATE

1

Amphibious vehicle steering

The present invention relates to amphibious vehicle stearing.

Bain Smith

Amphibious vehicles, hereafter "amphibians", are frequently steered in their land and marine modes by the same steering wheel. A simple form of amphibian steering is shown in US patent no. 5,727,494 (Caserta). In Caserta's proposal, a steering cable is arranged between a rear propulsion unit and the inner shaft of the steering column, which the cable is wound around, and thence back to the marine propulsion unit. Whilst this is a simple arrangement, it is unsuitable for high speed planing amphibians, where the force required to steer the propulsion unit is high. That is, the mechanical advantage of the Caserta arrangement is low. Where an automotive steering column is used, there is a high risk that the steering cable according to Caserta will conflict either with the mechanism designed to ensure crushability of the steering column in an accident; or alternatively, with any telescopic adjustment mechanism designed to ensure an ergonomic driving position.

In another proposal shown in US patent no. 5,590,617 (Gere), the linkages between the rear marine propulsion unit and the steering arrangement at the front of the vehicle are bulky and heavy, at a location at the front of the vehicle where weight has to be carefully controlled in a planing amphibian. Furthermore, the steering according to Gere is conformed so as to be operable in either a road mode or a marine mode. To allow this duality, the road steering system depends for operation on the steering rack being held in place by pressurized pneumatic rams. This is somewhat alarming from a safety viewpoint.

It is considered advantageous to have road and marine steering systems which can be operated simultaneously. This simplifies control systems, as there are less changes to be made in converting from road mode to marine mode or vice versa. Also, when manoeuvring at low speed in water, particularly to direct an amphibian to a slipway, the steering effect of dependent road wheels may be at least as great as that of, for example, a strering nozzle attached to a jet drive. Furthermore, if both systems can be operated together, there is no need for complex systems to ensure that when one or the other system is switched in, it is always initially centred. Finally, there is a safety advantage, in that in the unlikely event of breakage or seizure of the steering cable, a second steering system is

T

2

available. In this context, it should be noted that the marine steering is self-centring. In the absence of any control input or restraint of movement, passage of water through the jet steering nozzle will tend to centre the nozzle.

It is an object of the invention to provide a steering system for a planing amphibian in which the steering system is balanced, so that power assistance to the road steering matches the power assistance required to overcome the self centring tendency of the marine propulsion unit running at high speed. Another object is to reduce the bulk of parts of the steering assembly in the region between the front wheels, which have to retract to reduce water resistance in a planing amphibious vehicle.

According to the invention, there is provided an amphibious vehicle having retractable wheels and a planing hull, a marine propulsion unit, front wheels arranged to be steered by means of a power assisted transversely mounted element linked by means of a link for each wheel, the links arranged to fold upwards on retracting the wheels, an actuating rod mounted to said element, the rod arranged for transverse movement, and a flexible coupling means connecting said actuating rod to a steerable part of the marine propulsion unit, so that transverse movement of said element steers the part of the marine propulsion unit.

20

25

30

5

10

15

Preferably, both road and marine steering systems may be operated simultaneously. The transversely mounted element may be a rack and pinion steering system. The coupling means is preferably a push-pull cable and a bell-crank means attached to the actuating rod. The push-pull cable arrangement, comprising a cable slidable in a sleeve, is readily arranged so as to fit between body members and the vehicle power train with a minimum bending radius of 150mm. In one embodiment, the cable is between 12 and 13mm in diameter, whilst the outer sleeve of the cable is between 15 and 17mm in diameter.

The steering system may be readily adapted to a steering system comprising more than one steered front axle. It could also be adapted to a marine propulsion system comprising more than one marine propulsion unit.

D80: 25/04/03

0067279 25-Apr-03:04:31

An embodiment of the invention will now be described by way of example with reference to the following drawings in which:

Figure 1 is a perspective view from above and behind, of the front wheel steering arrangement of an amphibian with retractable wheels according to the invention;

Figure 2 is a side view of one front wheel arrangement of the amphibian of Figure 1 in road mode, with the front wheel removed for clarity;

Figure 3 is a side view of the front wheel arrangement of Figure 2, in the wheel retracted position in marine mode; and

Figure 4 is a plan view of a marine propulsion unit of the amphibian of Figure 1, as steered by the steering arrangement of Figure 1.

15

20

In the drawings, Figure 1 shows on the left the front wheel hub assembly 2 with brake disc 4 and brake caliper 6. The hub assembly 2 is mounted to upper and lower wishbones 8 and 9, which enable piston and cylinder arrangement 12 to raise the front wheel from the position shown in Figure 2 to that shown in Figure 3. In doing so, link 14 (there is the same arrangement on the other side, shown at 14') folds upwards to the position 14" shown in broken lines in Figure 1. (The folded position 14" is shown for link 14", for clarity). Figure 3 also shows part of the bull 10 to which wishbones 8 and 9 are mounted via a mounting plate (omitted for clarity). The hull 10 has a planing bottom 11.

Coupled to links 14 and 14' is power assisted transversely mounted steering rack unit 16, actuated by a pinion in housing 18; which in turn is actuated by an inner steering column on axis 20, and finally by a steering wheel 22, shown diagrammatically at a severely reduced scale for clarity.

The rack movement is some 114mm lock to lock, whilst the steering wheel has 2.3 turns from lock to lock. Mounted to rack arm 24 is bracket 26, to which is in turn mounted link rod 28; to the other end of which is mounted bell crank 30. Crank 30 is pivoted about pivot 32, and coupled to push-pull cable 34; which is slidably mounted in flexible casing

D80: 25/04/03

0067279 25-Apr-03 04:31

-445712 388888 G1888 1ECH

15

20

25

30

Bain Smith

or sleeve 36. The coupling between rack arm 24 and bell crank 30 is such that rod 28 is in front of steering column 20. This ensures economy of space.

At the rear of the vehicle is marine propulsion unit 40, shown in Figure 4, which has a steering nozzie 42 pivotally mounted to propulsion conduit housing 44 at 46. Bolted to said nozzle is steering arm 48, to which the push-pull cable is coupled. Sleeve 36 is fixedly secured at 50 to flange 52 of housing 44. Sleeve 36 is 15 to 17mm in diameter, whilst cable 34 is 12 to 13mm in diameter. The cable and sleeve are arranged in the vehicle with a minimum bending radius of 150mm. A reversing bucket may be fitted to the steering nozzle, as is known in the marine engineering art.

It should be noted that further refinements may be made to the steering system described above without departing from the essential inventive concept. For example, the system is particularly suited to be adapted to a road steering system using "steer by wire"; that is, not having a mechanical linkage between the steering wheel and the transversely mounted steering element. Such a system would be particularly advantageous to an amphibian, in that the bulkhead ahead of the driver would be more easily sealed against passage of water without a conventional steering column passing therethrough. The power assisted steering system may be hydraulic, hybrid hydraulic/electric, electric, or magnetic. The input to the marine steering system could be taken from a steered rear axle. This would, however, require some means of control which accounted for the fact that most rear wheel steering systems sometimes steer the rear wheels out of phase with the front wheels; and sometimes in phase with them.

Where two or more marine propulsion units are used, their steering nozzles may be mechanically linked to ensure that they turn in phase with each other. Such a linkage may have some geometry comparable to Ackermann geometry for road steering. Where two or more front steered axles are used, they may both have hydraulic cylinders to steer their respective wheels. With two steered front axles and two marine drives, a cable could be taken from each steered axle to a respective marine drive.

The fixing of the cable sleeve to the jet flange described above is a simple and cheap solution. It may be preferred to fix the cable sleeve to a jet flange by means of a

bracket and locknuts, thereby allowing longitudinal adjustment of the cable sleeve; as is known in the marine engineering art.

The steering system described offers a fixed ratio between road and marine steering, which is fixed at the design stage by the lengths of the arms on the bell crank. The drawback of such a fixed ratio is considered to be outweighed by the system's compactness, simplicity, and light weight; each of which are particularly helpful where retractable wheels are fitted.

10

- The Control

Claims

1. An amphibious vehicle having retractable wheels and a planing hull, a marine propulsion unit, front wheels arranged to be steered by means of a power assisted transversely mounted element linked by means of a link for each wheel, the links arranged to fold upwards on retracting the wheels, an actuating rod mounted to said element, the rod arranged for transverse movement, and a flexible coupling means connecting said actuating rod to a steerable part of the marine propulsion unit, so that transverse movement of said element steers the part of the marine propulsion unit.

10

- 2. An amphibious vehicle according to claim 1, wherein both road and marine steering systems may be operated simultaneously.
- 3. An amphibious vehicle according to claim 1 or claim 2, wherein the transversely
 15 mounted element is a rack and pinion steering system.
 - 4. An amphibious vehicle according to any of the above claims, wherein the coupling means is a push-pull cable.
- 5. An amphibious vehicle according to claim 4, wherein the push-pull cable is coupled to the actuating rod through a bell crank means.
- 6. An amphibious vehicle according to claim 5, wherein the bell crank means is
 connected to the transversely mounted element by means of a rod means mounted in front
 25 of a steering column.
 - 7. An amphibious vehicle according to any of the above claims, wherein more than one front steered axle is fitted.
- 30 8. An amphibious vehicle according to any of the above claims, wherein more than one steered marine propulsion unit is fitted.

9. An amphibious vehicle as herein described or as illustrated in any one or more of Figures 1, 2, 3, or 4.

5 .

ABSTRACT

Amphibious vehicle cable steering system

(fig. 1)

An amphibious vehicle has retractable wheels (figs. 2 and 3) attached to hubs 2, and a planing hull (10, 11, fig. 3). Front wheels are arranged to be steered by a power assisted transversely mounted element 16, which may be a rack and pinion unit. The element is linked to the wheels by links 14, 14', which fold up to position 14'' when the wheels are retracted. Actuating rod 28 is mounted to said element, and arranged for transverse movement. A flexible coupling means, such as cable 34 and sleeve 36, connects rod 28 to a steerable part (42, fig. 4) of a marine propulsion unit, to effect marine steering. Road and marine steering may be operable simultaneously. More than one front steered axle, and/or marine propulsion unit, may be fitted. The steering system is readily adapted to all kinds of power assisted steering, and also to "steer by wire".

0067279 25-Apr-03 04:31


26.Apr. 2003 12:02


10

17 Apr 03 14:40 · Bain Smith 01233712997

. 23 Apr. 2003 15:20 *** **** 388868 GIBBS TECH

17 Apr 03 14:40 Bain Smith 01233712997 01233712997






*442476 388868 GIBBS TECH

1S:81.8003 .19A-6S





PGT/GB2004/001697

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:
☐ BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
OTHER:

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.